

MONTCLAIR STATE UNIVERSITY UNIVERSITY HALL COURTYARD LIGHTING UPGRADE

1 NORMAL AVENUE, MONTCLAIR, NJ 07043

MSU PROJECT NUMBER: 16C011.3

NOVEMBER, 2025

GENERAL PROJECT INFORMATION	
OWNER:	MONTCLAIR STATE UNIVERSITY
AUTHORITY HAVING JURISDICTION:	MONTCLAIR, NJ
CODE REVIEW	
BUILDING:	INTERNATIONAL BUILDING CODE / 2021 WITH NJ AMENDMENTS
ELECTRICAL:	NATIONAL ELECTRIC CODE (NFPA 70) / 2020
PLUMBING:	NATIONAL STANDARD PLUMBING CODE / 2021
MECHANICAL:	INTERNATIONAL MECHANICAL CODE (IMC 2021) / 2021
FIRE PROTECTION:	INTERNATIONAL FIRE CODE / 2015
FUEL GAS:	INTERNATIONAL FUEL GAS CODE / 2021
REHABILITATION:	NJ UCC, N.J.A.C. 5:23-6, SUBCHAPTER 6
BARRIER FREE:	NJIBC 2015 CHAPTER 11 AND NJIBC 2018 CHAPTER 11 AND NJAC 5:23-7, ICC/ANSI A117.1-2017
ENERGY:	ASHRAE 90.1-2019





DRAWING INDEX		
SHEET NUMBER	SHEET NAME	SHEET DESCRIPTION
GENERAL		
1	T-001	TITLE
2	G-001	GENERAL NOTES, LEGENDS, AND ABBREVIATIONS
DEMOLITION		
3	D-101	DEMOLITION FLOOR PLAN
ARCHITECTURAL		
4	A-101	NEW WORK FLOOR PLAN
ELECTRICAL		
5	E-001	GENERAL NOTES, LEGENDS, AND ABBREVIATIONS
6	E-101	NEW WORK FLOOR PLAN
7	E-401	SCHEDULES
8	E-501	DETAILS
9	E-601	SINGLE LINE DIAGRAM



A/E FIRM



crane associates, p.c.
consulting engineers / architects
92 East Main Street, Suite 200 Somerville, NJ 08876-3109
Tel: (908) 203-8788 Fax: (908) 203-8199
CRANE PROJECT NUMBER: 6780-2501



VICINITY MAP



LOCALITY MAP



crane associates, p.c.
consulting engineers / architects
92 East Main Street, Suite 200 Somerville, NJ 08876-3109
www.craneassociates.com
Dennis George Link, AIA
Registered Architect, NJ Lic. No. Z140/937600
Date: _____

MSU COURTYARD LIGHTING
UNIVERSITY HALL
1 NORMAL AVENUE
MONTCLAIR, NJ 07043

GENERAL
TITLE

PROJECT NO.
6780-2501
DRAWING NO.
T-001
DWG 1 OF 9

DESIGNED DGL
DRAWN SG
CHECKED DGL
SCALE AS SHOWN
DATE 10/20/2025
NO. BY CK DATE REVISION N

GENERAL ARCHITECTURAL NOTES

- ALL WORK PERFORMED SHALL BE IN COMPLIANCE WITH ALL APPLICABLE CODES AND REQUIREMENTS OF FEDERAL, STATE AND LOCAL GOVERNING AGENCIES HAVING JURISDICTION.
- THE OWNER RESERVES THE RIGHT TO DESIGNATE THE ORDER IN WHICH THE CONTRACTOR SHALL PROCEED WITH ANY AND ALL PORTIONS OF THE WORK. WORK SHALL BE COORDINATED SO AS NOT TO INTERFERE WITH THE BUILDING OCCUPANTS AND ACTIVITIES. PRIOR TO BEGINNING WORK, THE CONTRACTOR SHALL SUBMIT A CONSTRUCTION SCHEDULE SHOWING HOW THE WORK WILL PROCEED DURING THE CONSTRUCTION PERIOD. THE CONSTRUCTION SCHEDULE SHALL INCLUDE ANY WORK REQUIRED TO BE PHASED. THIS SHALL BE SUBMITTED FOR REVIEW AND APPROVAL BY THE OWNER AND THE OWNER'S REPRESENTATIVE.
- THE CONTRACTOR AND THEIR TRADE SUBCONTRACTORS SHALL BE RESPONSIBLE FOR VISITING THE SITE AND FAMILIARIZING THEMSELVES WITH ALL EXISTING CONDITIONS PRIOR TO SUBMITTING THEIR BID.
- THE CONTRACTOR SHALL COORDINATE ALL STAGING AREAS WITH THE OWNER'S REPRESENTATIVE PRIOR TO STARTING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR COORDINATION OF ALL WORK UNDER THIS CONTRACT TO ENSURE THE QUALITY AND TIMELY COMPLETION OF THE WORK / PROJECT. THE CONTRACTOR SHALL COORDINATE ALL AREAS OF WORK WITH OTHER TRADES INVOLVED WITH THE PROJECT.
- GENERAL CONTRACTOR WILL OBTAIN ALL PERMITS AND ARRANGE FOR PAYMENT OF PERMIT AND FILING FEES WITH OWNER.
- THE CONTRACTOR SHALL PROPERLY PROTECT AND MAKE SAFE ADJACENT PROPERTY/STRUCTURE AS REQUIRED BY JOB CONDITIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO ISOLATE ALL WORK AREAS AND CLEARLY DEFINE PATHS OF ACCESS TO THE WORK FOR THE WORKMEN IN ORDER TO INSURE MINIMIZATION OF DUST INFILTRATION TO OTHER AREAS OF THE BUILDING AND TO PREVENT DAMAGE TO FLOORS, WALLS AND CEILINGS OF PUBLIC AND/OR FREIGHT ACCESS AREAS. IF SUCH DAMAGE SHOULD OCCUR, CONTRACTOR SHALL CORRECT THE DAMAGE IMMEDIATELY AT THEIR OWN COST.
- THE CONTRACTOR SHALL PROVIDE NOT LESS THAN ONE ORDINARY HAZARD FIRE EXTINGUISHER AT EACH STAIRWAY OR OTHER MEANS OF EGRESS ON ALL FLOOR LEVELS WHERE COMBUSTIBLE MATERIALS HAVE ACCUMULATED.
- ALL PRECAUTIONS SHALL BE TAKEN TO PREVENT DIRT, NOISE, WATER AND DUST FROM ENTERING OTHER PARTS OF THE BUILDING DURING THE PROGRESS OF THE WORK.
- EACH TRADE SUBCONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING THE WORK SITE FREE FROM DEBRIS AND ACCUMULATED REFUSE. EACH TRADE SUBCONTRACTOR SHALL HAVE SOLE RESPONSIBILITY FOR PROTECTING ALL AREAS FROM ENTRY BY UNAUTHORIZED PARTIES. SITE WILL BE LEFT BROOM CLEAN AT THE END OF EACH WORK DAY.
- THE CONTRACTOR SHALL MAINTAIN FREE AND UNOBSTRUCTED ACCESS FROM WORK AREA AND ADJACENT SPACES TO THE OUTSIDE OF THE BUILDING AT ALL TIMES. IF THE PATHS OF EGRESS CANNOT BE MAINTAINED DURING CONSTRUCTION, THEN THE CONTRACTOR SHALL PROVIDE ALTERNATE MEANS OF EGRESS INCLUDING ERECTING BARRICADES, TEMPORARY SIGNS, ALTERNATE PATHS OF TRAVEL, ETC. IN ORDER TO MAINTAIN A SAFE WORK ENVIRONMENT FOR THE BUILDING OCCUPANTS AND VISITORS.
- THE CONTRACTOR SHALL PROVIDE PROTECTION AT SIDEWALKS AND CURBS AROUND THE PREMISES SO THAT SAME MAY BE SAFELY USED BY THE PUBLIC AT ALL TIMES AND AS REQUIRED BY CODE AND ALL AGENCIES HAVING JURISDICTION.
- THE CONTRACTOR SHALL PROVIDE BARRICADES AROUND WORK AREAS AS REQUIRED TO PREVENT BUILDING EMPLOYEES AND OTHER UNAUTHORIZED PERSONS FROM ENTERING THEREIN.
- THE CONTRACTOR SHALL PROVIDE GUARDS, RAILS, BARRICADES, FENCES, SIDEWALK SHEDS, CATCH PLATFORMS, DECKING, NIGHT LIGHTING, AS REQUIRED BY CODE AND ALL AGENCIES HAVING JURISDICTION, AND AS REQUIRED TO PROVIDE ADEQUATE PROTECTION.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ADEQUATELY BRACING AND PROTECTING ALL WORK DURING CONSTRUCTION AGAINST DAMAGE, BREAKAGE, COLLAPSE, DISTORTIONS, AND OFF ALIGNMENTS ACCORDING TO CODE AND STANDARDS OF GOOD CONSTRUCTION PRACTICE.
- DRAWINGS SHALL NOT BE SCALED. USE DIMENSIONS ONLY. ALL DIMENSIONS AND CONDITIONS SHOWN AND ASSUMED ON THE DRAWINGS MUST BE VERIFIED AT THE SITE BY THE CONTRACTOR BEFORE ORDERING ANY MATERIAL OR START OF ANY WORK. WHERE DISCREPANCIES OCCUR AND/OR WHERE THERE ARE CONFLICTS OR OMISSIONS IN THE DRAWINGS, SPECIFICATIONS AND APPLICATIONS, CONTRACTOR SHALL NOTIFY THE OWNER'S REPRESENTATIVE IMMEDIATELY AND REFRAIN FROM STARTING AND COMPLETING SUCH WORK, OR DEPENDENT WORK, UNTIL DIRECTED BY THE OWNER'S REPRESENTATIVE TO PROCEED. NO CHANGE IN DRAWINGS OR SPECIFICATIONS IS PERMISSIBLE WITHOUT THE WRITTEN CONSENT OF THE OWNER'S REPRESENTATIVE. U.O.N. ALL DIMENSIONS ARE GIVEN TO THE FINISHED FACE OF THE STUD, PARTITION OR MASONRY WALL. CLEAR AND MINIMUM DIMENSIONS ARE GIVEN TO FACE OF WALL OR FLOOR FINISHES.
- DETAILS NOT SHOWN OR SPECIFIED HERE, BUT NECESSARY FOR PROPER AND ACCEPTABLE CONSTRUCTION, INSTALLATION OR OPERATION FOR ANY PART OF THE WORK SHALL BE INCLUDED IN THE WORK THE SAME AS IF HEREIN SPECIFIED OR INDICATED.
- SUBCONTRACTORS ARE RESPONSIBLE FOR OBTAINING FROM THE GENERAL CONTRACTOR ALL DRAWINGS AND SPECIFICATIONS PERTINENT TO THEIR SCOPE OF WORK TO PROPERLY BID AND CONSTRUCT THIS PROJECT.
- SUBCONTRACTORS ARE RESPONSIBLE FOR REVIEWING ALL DRAWINGS FOR THIS PROJECT. A COMPLETE LIST OF DRAWINGS CAN BE FOUND IN THE INDEX OF SHEET T-001.
- THE INFORMATION SHOWN ON THE CONTRACT DRAWINGS IS BASED ON LIMITED EXISTING CONDITION BUILDING DRAWINGS, LIMITED FIELD SURVEY AND LIMITED VISUAL OBSERVATION. EACH TRADE SUBCONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND EXISTING STRUCTURE/BUILDING INFORMATION IN FIELD PRIOR TO START OF THE CONTRACT WORK.
- REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- IF ANY HAZARDOUS MATERIALS ARE ENCOUNTERED, THE CONTRACTOR SHALL STOP WORK AND SHALL NOTIFY THE OWNER'S REPRESENTATIVE IMMEDIATELY.
- THE CONTRACTOR SHALL PERFORM ALL CUTTING AND PATCHING REQUIRED TO COMPLETE THE WORK OR TO MAKE ITS PARTS FIT TOGETHER PROPERLY WITHOUT COMPROMISING THE QUALITY OF THE WORK. MATERIALS USED FOR PATCHING & REPAIRING SHALL MATCH EXISTING MATERIALS, UNLESS NOTED OTHERWISE.
- ALL EXISTING AND NEWLY CONSTRUCTED SURFACES SHALL BE PROTECTED FROM DEMOLITION/CONSTRUCTION ACTIVITIES. WHERE EXISTING FINISHES ARE CUT OR ALTERED, THEY SHALL BE MODIFIED IN SUCH A MANNER THAT AFTER ASSEMBLY THEY PROVIDE A COMPLETE CONTINUOUS FINISHED CONDITION.
- IN GENERAL, NEW MATERIALS USED FOR REPAIR CONDITIONS SHALL MATCH SIMILAR ITEMS IN QUALITY, DETAIL, PROFILE AND FINISH AS THOSE ALREADY BUILT INTO THE WORK, UNLESS OTHERWISE NOTED.
- THE CONTRACTOR SHALL LAY OUT THEIR OWN WORK AND SHALL COORDINATE WITH AND VERIFY ALL DIMENSIONS REQUIRED BY OTHER TRADE SUBCONTRACTORS.
- ALL WORK SHALL BE INSTALLED SO THAT ALL PARTS REQUIRED ARE READILY ACCESSIBLE FOR INSPECTION, OPERATION, MAINTENANCE AND REPAIR.
- THE WORDS "PROVIDE" OR "PROVIDE NEW" SHALL MEAN TO SUPPLY AND INSTALL NEW ITEM(S) AND/OR SYSTEM(S) AS INDICATED.
- THE TERM "FINISH FLOOR" SHALL MEAN THE NORMAL FINISHED SURFACE OF THE FLOOR LEVEL.
- THE CONTRACTOR SHALL PATCH AND REPAIR ALL SURFACES DUE TO, BUT NOT LIMITED TO, THE DEMOLITION. ALL PENETRATIONS SHALL BE SEALED, CAPPED AND LEVELED SMOOTH TO MATCH ADJACENT MATERIALS, UNLESS OTHERWISE NOTED.
- WHERE MANUFACTURER'S NAMES AND PRODUCT NUMBERS ARE INDICATED ON THE DRAWINGS IT SHALL BE CONSTRUED TO MEAN THE ESTABLISHING OF QUALITY AND PERFORMANCE STANDARDS OF SUCH ITEMS. ALL PRODUCT SUBSTITUTIONS SHALL BE SUBMITTED TO THE OWNER'S REPRESENTATIVE WITH A DEDUCT CHANGE ORDER FOR APPROVAL.

GENERAL ARCHITECTURAL NOTES (CONT'D)

- ALL PLUMBING, ELECTRICAL AND OTHER TRADE CONTRACT WORK REQUIRING THE USE OF LICENSED PERSONNEL SHALL BE PERFORMED BY LICENSED CONTRACTORS.
- THE CONTRACTOR SHALL PROVIDE SLEEVES AND FIRE SEALANT AROUND ALL NEW, THROUGH WALL PENETRATIONS IN FIRE RATED WALLS. SEE MECHANICAL, ELECTRICAL, FIRE PROTECTION AND PLUMBING DRAWINGS. SEAL ALL PENETRATIONS THROUGH FIRE RATED WALLS WITH UL APPROVED FIRE RATED SYSTEMS.
- IN THE EVENT OF CONFLICTS OR INCONSISTENCIES WITHIN OR BETWEEN PARTS OF THE CONTRACT DOCUMENTS, OR BETWEEN THE CONTRACT DOCUMENTS AND APPLICABLE STANDARDS, CODES AND ORDINANCES, THE CONTRACTOR SHALL (1) PROVIDE THE BETTER QUALITY OR GREATER QUANTITY OF WORK, OR (2) COMPLY WITH THE MORE STRINGENT REQUIREMENT OR PROVIDE THE MORE EXPENSIVE METHOD, MATERIAL OR FINISH SYSTEM; EITHER OR BOTH IN ACCORDANCE WITH THE ARCHITECT'S INTERPRETATION.
- CONTRACTOR SHALL FIELD EXAMINE ALL EXISTING BUILDING UTILITIES, WHICH ARE SHOWN ON DRAWINGS TO BE REUSED, SUCH AS PIPING, DUCTWORK, FLUE PIPES, ELECTRICAL CONNECTIONS, ETC. FOR CODE COMPLIANCE. CONTRACTOR SHALL REPAIR, REPLACE, OR PROVIDE NEW COMPONENTS AT ANY DAMAGED OR MISSING CODE REQUIRED COMPONENTS, INCLUDING BUT NOT LIMITED TO PIPE/DUCT SUPPORTS, FIRE DAMPERS, PIPING/DUCTWORK INSULATION, ETC. CONTRACTOR SHALL NOTIFY THE OWNER'S REPRESENTATIVE IMMEDIATELY OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK.
- IF THE CONTRACTOR VIOLATES OR IS NON-COMPLIANT WITH ANY CODES, LAWS, ORDINANCES OR REGULATIONS IN PERFORMING THE WORK, THEN THE CONTRACTOR SHALL, AT THEIR OWN EXPENSE, BEAR ALL PENALTIES AND COSTS AND SHALL INDEMNIFY AND HOLD HARMLESS THE OWNER AND EI ASSOCIATES AGAINST ANY CLAIMS, DEMANDS, SUITS, DAMAGES, COSTS AND EXPENSES THAT MAY RESULT FROM SUCH VIOLATIONS.
- CRANE ASSOCIATES SHALL NOT BE RESPONSIBLE FOR AND SHALL NOT HAVE CONTROL OR CHARGE OF CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES OR FOR SAFETY PRECAUTIONS AND PROGRAMS IN CONNECTION WITH THE WORK. CRANE ASSOCIATES SHALL NOT BE RESPONSIBLE FOR CONTRACTOR'S FAILURE TO CARRY OUT THE WORK IN ACCORDANCE WITH THESE DESIGN DOCUMENTS OR FOR THE CONTRACTOR'S FAILURE TO PROVIDE SERVICES IN A PROFESSIONAL MANNER IN ACCORDANCE WITH STANDARDS OF GOOD PRACTICE. CRANE ASSOCIATES SHALL NOT BE RESPONSIBLE FOR OR HAVE CHARGE OVER THE ACTS AND/OR OMISSIONS OF THE CONTRACTORS, SUBCONTRACTORS OR ANY OF THEIR AGENTS OR EMPLOYEES OR ANY PERSON PERFORMING THE WORK.
- CRANE ASSOCIATES SHALL NOT BE RESPONSIBLE FOR AND SHALL NOT HAVE CONTROL OR CHARGE OF CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES OR FOR SAFETY PRECAUTIONS AND PROGRAMS IN CONNECTION WITH THE WORK. CRANE ASSOCIATES SHALL NOT BE RESPONSIBLE FOR CONTRACTOR'S FAILURE TO CARRY OUT THE WORK IN ACCORDANCE WITH THESE DESIGN DOCUMENTS OR FOR THE CONTRACTOR'S FAILURE TO PROVIDE SERVICES IN A PROFESSIONAL MANNER IN ACCORDANCE WITH STANDARDS OF GOOD PRACTICE. CRANE ASSOCIATES SHALL NOT BE RESPONSIBLE FOR OR HAVE CHARGE OVER THE ACTS AND/OR OMISSIONS OF THE CONTRACTORS, SUBCONTRACTORS OR ANY OF THEIR AGENTS OR EMPLOYEES OR ANY PERSON PERFORMING THE WORK.

crane associates, p.c.
CONSULTING ENGINEERS / ARCHITECTS
92 East Main Street, Suite 200, Somerville, NJ 08876-3109
www.craneassociates.com
Dennis George Link, AIA
Registered Architect, NJ Lic. No. Z140-1957600
Date: _____


MSU COURTYARD LIGHTING
UNIVERSITY HALL
1 NORMAL AVENUE
MONTCLAIR, NJ 07043

GENERAL NOTES, LEGENDS, AND ABBREVIATIONS
GENERAL PROJECT NO.
DRAWING NO.
G-001
DWG 2 OF 9

PROJECT NO.
6780-2501

DRAWING NO.
G-001


DWG 2 OF 9




1 UNIVERSITY HALL COURTYARD DEMOLITION FLOOR PLAN

Scale: 3/16" = 1'-0"

4 0 4 8



Scale: 1-1/2" = 1'-0"



Scale: 1-1/2" = 1'-0"

GENERAL NOTES

- A. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND REPORT ANY DISCREPANCIES TO THE PROJECT MANAGER AND THE OWNER'S CONSTRUCTION REP.
- B. ALL MATERIALS, INSTALLATION, AND WORKMANSHIP SHALL COMPLY WITH ALL APPLICABLE STATE AND CITY CODES AND ORDINANCES, INDUSTRY STANDARDS, UTILITY COMPANY REGULATIONS AND ALL REQUIREMENTS OF LOCAL AND FEDERAL AUTHORITIES HAVING JURISDICTION.
- C. CONTRACTORS SHALL BE RESPONSIBLE FOR ADHERING TO ALL MONTCLAIR STATE UNIVERSITY REQUIREMENTS AND GUIDELINES GOVERNING WORK PERFORMED IN OCCUPIED SPACES. ALL ISSUES SHALL BE COORDINATED WITH THE PROJECT MANAGERS PRIOR TO CONSTRUCTION.
- D. IF HAZARDOUS MATERIALS ARE IN ANY WAY SUSPECTED INCLUDING BUT NOT LIMITED TO ASBESTOS OR POLLUTANTS, CONTRACTOR SHALL INFORM THE PROJECT MANAGER IMMEDIATELY AND SUSPEND WORK ON THAT AREA OF CONSTRUCTION.
- E. CONTRACTOR SHALL COORDINATE STORAGE OF BUILDING MATERIALS AND THE REMOVAL AND CLEAN-UP OF ALL DEBRIS CAUSED BY WORK DURING CONSTRUCTION. CLEAN ALL AREAS TO "AS-IS" CONDITION AT THE END OF EACH WORK DAY.
- F. CONTRACTORS ARE TO CONFINE CONSTRUCTION TRAFFIC AND DEBRIS REMOVAL TO THE CONSTRUCTION AREA AS MUCH AS POSSIBLE TO MINIMIZE DUST MIGRATION. ERECT DUST PARTITIONS WHERE DEMOLITION AND/OR NEW CONSTRUCTION ABUTS EXISTING FINISHED SPACES.
- G. CONTRACTOR SHALL COORDINATE ALL DEMOLITION WORK AND NEW CONSTRUCTION WORK WITH THE PROJECT MANAGER AND BUILDING MANAGEMENT TO MINIMIZE BUSINESS DISRUPTIONS WHILE NEW CONSTRUCTION IS IN PROGRESS.
- H. SEE ELECTRICAL DRAWINGS, ETC., FOR ADDITIONAL WORK TO BE COORDINATED WITH THIS DRAWING AND THE REQUIREMENTS SPECIFIED HEREIN.
- I. CONTRACTOR SHALL PATCH ALL WALL, CEILING, AND FLOOR SURFACES, AS WELL AS ANY OTHER MATERIALS TO REMAIN THAT ARE DAMAGED OR AFFECTED BY DEMOLITION OR NEW CONSTRUCTION. ALL PATCHING OF EXISTING CONSTRUCTION SHALL MATCH EXISTING MATERIALS AND FINISHES, UNLESS NOTED OTHERWISE.
- K. CONTRACTORS SHALL FIELD VERIFY ALL SITE CONDITIONS PRIOR TO SUBMITTING THEIR BID.
- L. PLANTINGS, EXTERIOR FURNITURE, AND PAVER BRICKS EXISTING TO REMAIN. PROTECT DURING CONSTRUCTION.

ARCHITECTURAL DEMOLITION KEYED NOTES

ADD1 VEGETATION AND SOIL TO BE REMOVED DOWN TO EXISTING STRUCTURAL DECK AT EACH POST LOCATION. COORDINATE WITH ELECTRICAL SCOPE FOR CONDUIT ROUTING. STOCKPILE SOIL DURING CONSTRUCTION OUTSIDE OF AREA OF WORK.

DUST PROTECTION NOTES


- A. COORDINATE ALL WORK WITH OTHER TRADES.
- B. ALL DUST PROTECTION TO BE CONSTRUCTED WITH FIRE RETARDANT #2 FIR.
- C. ALL DUST PROTECTION FRAMING MEMBERS TO BE FIELD MEASURED, AND SAW CUT IN TEMPORARY STAGING AREA OUTSIDE AND AWAY FROM BUILDING ENTRY AND SWITCHING EQUIPMENT.
- D. BRUSH CLEAN ALL MATERIALS AFTER BEING CUT, AND WIPE CLEAN EACH FRAMING MEMBER FREE OF ALL LOOSE PARTICLES PRIOR TO BRINGING INTO THE BUILDING FOR ERECTION.
- E. PROVIDE DUST PROTECTION AT ALL LOCATIONS OF DEMOLITION AND ALL NEW OR MODIFICATION WORK. COORDINATE SCOPE AND LOCATION WITH OTHER TRADES AND VERIFY IN FIELD ACTUAL CONDITIONS.
- F. CONTRACTOR IS RESPONSIBLE FOR COORDINATING AND INSTALLING DUST AND EQUIPMENT PARTITIONS TO PROTECT IN SERVICE EQUIPMENT WITHIN THE AREA OF WORK TO PREVENT DUST/DEBRIS MIGRATION REQUIREMENTS. PROTECTION SHALL NOT INTERFERE WITH OWNERS' INGRESS AND EGRESS OR EQUIPMENT OPERATION AND MAINTENANCE.
- G. PROVIDE CONTINUOUS DUST PROTECTION BARRIER WITH FIRE RETARDANT ANTI-STATIC FILM SHEETING. SHEETING TO COMPLY WITH NFPA 701. TAPE ALL SEAMS AS RECOMMENDED BY MANUFACTURER.

MSU COURTYARD LIGHTING
UNIVERSITY HALL
1 NORMAL AVENUE
MONTCLAIR, NJ 07043

DEMOLITION FLOOR PLAN
DEMOLITION FLOOR PLAN

PROJECT NO.
6780-2501
DRAWING NO.
D-101
DWG. 3 OF 9

crane associates, p.c.
consulting engineers / architects
92 East Main Street, Suite 200, Somerville, NJ 08876-3109
www.craneassociates.com
Dennis George Link, AIA
Registered Architect, NJ Lic. No. Z1401997600
Date: 10/20/2025



1 UNIVERSITY HALL COURTYARD NEW WORK FLOOR PLAN


Scale: 3/16" = 1'-0"

GENERAL NOTES

- A. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND REPORT ANY DISCREPANCIES TO THE PROJECT MANAGER AND THE OWNER'S CONSTRUCTION REP.
- B. ALL MATERIALS, INSTALLATION, AND WORKMANSHIP SHALL COMPLY WITH ALL APPLICABLE STATE AND CITY CODES AND ORDINANCES, INDUSTRY STANDARDS, UTILITY COMPANY REGULATIONS AND ALL REQUIREMENTS OF LOCAL AND FEDERAL AUTHORITIES HAVING JURISDICTION.
- C. CONTRACTORS SHALL BE RESPONSIBLE FOR ADHERING TO ALL MONTCLAIR STATE UNIVERSITY REQUIREMENTS AND GUIDELINES GOVERNING WORK PERFORMED IN OCCUPIED SPACES. ALL ISSUES SHALL BE COORDINATED WITH THE PROJECT MANAGERS PRIOR TO CONSTRUCTION.
- D. IF HAZARDOUS MATERIALS ARE IN ANY WAY SUSPECTED INCLUDING BUT NOT LIMITED TO ASBESTOS OR POLLUTANTS, CONTRACTOR SHALL INFORM THE PROJECT MANAGER IMMEDIATELY AND SUSPEND WORK ON THAT AREA OF CONSTRUCTION.
- E. CONTRACTOR SHALL COORDINATE STORAGE OF BUILDING MATERIALS AND THE REMOVAL AND CLEAN-UP OF ALL DEBRIS CAUSED BY WORK DURING CONSTRUCTION. CLEAN ALL AREAS TO "AS-IS" CONDITION AT THE END OF EACH WORK DAY.
- F. CONTRACTORS ARE TO CONFINE CONSTRUCTION TRAFFIC AND DEBRIS REMOVAL TO THE CONSTRUCTION AREA AS MUCH AS POSSIBLE TO MINIMIZE DUST MIGRATION. ERECT DUST PARTITIONS WHERE DEMOLITION AND/OR NEW CONSTRUCTION ABUTS EXISTING FINISHED SPACES.
- G. CONTRACTOR SHALL COORDINATE ALL DEMOLITION WORK AND NEW CONSTRUCTION WORK WITH THE PROJECT MANAGER AND BUILDING MANAGEMENT TO MINIMIZE BUSINESS DISRUPTIONS WHILE NEW CONSTRUCTION IS IN PROGRESS.
- H. SEE ELECTRICAL DRAWINGS, ETC., FOR ADDITIONAL WORK TO BE COORDINATED WITH THIS DRAWING AND THE REQUIREMENTS SPECIFIED HEREIN.
- I. CONTRACTOR SHALL PATCH ALL WALL, CEILING, AND FLOOR SURFACES, AS WELL AS ANY OTHER MATERIALS TO REMAIN THAT ARE DAMAGED OR AFFECTED BY DEMOLITION OR NEW CONSTRUCTION. ALL PATCHING OF EXISTING CONSTRUCTION SHALL MATCH EXISTING MATERIALS AND FINISHES, UNLESS NOTED OTHERWISE.
- K. CONTRACTORS SHALL FIELD VERIFY ALL SITE CONDITIONS PRIOR TO SUBMITTING THEIR BID.
- L. PLANTINGS, EXTERIOR FURNITURE, AND PAVER BRICKS EXISTING TO REMAIN. PROTECT DURING CONSTRUCTION.

ARCHITECTURAL NEW WORK KEYED NOTES

- A01 NEW FESTOON LIGHTING. REFER TO SHEET E-101 FOR MORE INFORMATION.
- A02 NEW WOOD POST. SEE DETAILS 2 AND 3, THIS SHEET.
- A03 NEW CASTSTONE SURROUND. SEE DETAIL 3, THIS SHEET.
- A04 EXISTING PAVER BRICK TO REMAIN. REPAIR AND REPLACE WHERE REQUIRED.
- A05 ELECTRICAL CONDUIT. CONFIRM LOCATION WITH ELECTRICAL DRAWINGS.



1 POST DETAIL WITH CONNECTION

Scale: 1/2" = 1'-0"

3 POST BASE DETAIL

Scale: 1/2" = 1'-0"

MSU COURTYARD LIGHTING
UNIVERSITY HALL
1 NORMAL AVENUE
MONTCLAIR, NJ 07043

ARCHITECTURAL
NEW WORK FLOOR PLAN

PROJECT NO.
6780-2501
DRAWING NO.
A-101
DWG. 4 OF 9

crane associates, p.c.
CONSULTING ENGINEERS/ARCHITECTS
92 East Main Street, Suite 200, Somerville, NJ 08876-3109
www.craneassociates.com
E-mail: info@craneassociates.com
Register of Architects of New Jersey No. 240619456000
Date: 10/21/2025

DESIGNED DGL
DRAWN SG
CHECKED DGL
SCALE AS SHOWN
DATE 10/21/2025
NO. BY CK DATE REVISION

GENERAL ELECT. LEGEND	
SYMBOL	DESCRIPTION
	20A 120/277V TWO POLE SWITCH HUBBELL 1221, MOUNT 3'-4" AFF X DENOTES THE SWITCHING CIRCUIT
	20A 120/277V THREE WAY SWITCH HUBBELL 1223, MOUNT 3'-4" AFF X DENOTES THE SWITCHING CIRCUIT
	20A 120/277V FOUR WAY SWITCH HUBBELL 1224, MOUNT 3'-4" AFF X DENOTES THE SWITCHING CIRCUIT
	FRACTIONAL HP MOTOR SWITCH - SNAP SWITCH X DENOTES THE SWITCHING CIRCUIT
	120/277V WALL MOUNTED OCCUPANCY SENSOR BY LEVITON ODS10-1D-DECORA WALL SWITCH WITH PIR X DENOTES THE SWITCHING CIRCUIT
	20A 125V DUPLEX GROUNDING OUTLET HUBBELL 5362-I, SEE MTG SPECIFICATIONS
	20A 125V DUPLEX GROUND FAULT OUTLET HUBBELL 5362-R, MOUNT 3'-6" AFF
	20A 125V DUPLEX GROUNDING OUTLET HUBBELL 5362-I, SEE MTG. SPECIFICATIONS WP DENOTES WEATHERPROOF GFI WITH "WHILE IN USE" COVERS.
	CLOCK OUTLET GROUNDING HUBBELL 5361-I, MOUNT 7'-0" AFF
	WELDING OUTLET
	WEATHER PROTECTED CONSTRUCTION NEMA 4
	CORROSION RESISTANT CONSTRUCTION NEMA 4X
	NON-FUSED DISCONNECT SWITCH RATING AS SHOWN, SEE SPECIFICATIONS
	FUSED DISCONNECT SWITCH RATING AS SHOWN, SEE SPECIFICATIONS
	COMBINATION DISCONNECT SWITCH AND STARTER
	VARIABLE FREQUENCY DRIVE DISCONNECT
	VARIABLE FREQUENCY DRIVE
	FULL VOLTAGE NON-REVERSING MOTOR STARTER
	CONDUIT
	CONDUIT UP
	CONDUIT DOWN
	SQUIRREL CAGE MOTOR X DENOTES HORSEPOWER RATING
	POWER PANEL 208V OR 480V PANEL
	AUTOMATIC TRANSFER SWITCH
	MAIN CIRCUIT BREAKER
	MAIN DISTRIBUTION PANEL
	HOMERUN ARROW INDICATES HOMERUN TO POWER PANEL, DISTRIBUTION PANEL, OR MCC 'XX' DENOTES DESIGNATED PANEL
	LOUVER OR DAMPER MOTOR OPERATOR BY HVAC CONTRACTOR, WIRED BY ELECT. CONTRACTOR
	UTILITY METER
	MANUAL MOTOR STARTER, SEE SPECS FOR TYPE & WIRING DIAGRAM FOR CONTROLS
	JUNCTION BOX SIZED PER THE NEC
	JUNCTION BOX FOR HEAT TRACING: COOLING TOWER PIPING
	STEP DOWN TRANSFORMER
	TYPE A EXTERIOR LIGHT FIXTURE MTD TO COOLING TOWER, SEE SPEC 26560-2.2A FOR DESCRIPTION, CATALOG NO., & MANUFACTURER.
	PHOTO CELL TORK No 2000-7, RATED FOR 120/277V, MOUNT ABOVE ROOF
	P-1 DOCK TRUCK LED LIGHT, IMPACT RESISTANT.
	INFRARED SENSOR FOR DOCK DOOR
	ELECTRICAL UTILITY POLE
	ELECTRICAL UTILITY OVERHEAD CABLE
	UNDERGROUND ELECTRICAL
	TEST WELL
	GROUND TRIAD WITH TEST WELL

GENERAL LEGEND	
TYPE	DESCRIPTION
	LETTER INDICATES DISCIPLINE (MECHANICAL, ELECTRICAL, ETC) M03
	DRAWING KEY NOTE DESIGNATION WITH LETTER 'D' ADDED INDICATES DEMOLITION
	DETAIL NUMBER D-02
	DETAIL
	SHEET NUMBER DETAIL IS ON
	DEMOLITION WORK
	EXISTING WORK
	NEW WORK
	MATCH LINE

ABBREVIATIONS

A	AMPERE(S)	GRND	GROUNDING	R	REMOVE
AC	ALTERNATING CURRENT	GUH	GAS UNIT HEATER	(R)	RECEPTE
A/E	ARCHITECT/ENGINEER	H	HAND HOLE	RECPT	RECEPTE
AF	AMPERE FRAME	HH	HIGH INTENSITY DISCHARGE	REPO	REMOTE EMERGENCY POWER SHUTOFF
AFC	ABOVE FINISHED CEILING	HID	HIGH INTENSITY DISCHARGE	REQ, REQD	REQUIRED
AFF	ABOVE FINISHED FLOOR	HOA	HAND-OFF-AUTOMATIC SWITCH	RF	RETURN FAN
AFG	ABOVE FINISHED GRADE	HP	HORSEPOWER	RIM	READER INTERFACE MODULE
AFU	AMPERE FUSE	HT	HEIGHT	RM	ROOM
AHJ	AUTHORITY HAVING JURISDICTION	HWP	HOT WATER PUMP	RO	REVERSE OSMOSIS
AIC	AMPERE INTERRUPTING CAPACITY	HV	HIGH VOLTAGE	RP	RECEPTE PANEL
AL	ALUMINUM	HZ	HERTZ	RVAT	REDUCED VOLTAGE TRANSFORMER
AS	AMMETER SWITCH			RTU	REMOTE TERMINAL UNIT
AM	AMMETER			RUPS	ROTARY UNINTERRUPTIBLE POWER SUPPLY
ANN	ANNUNCIATOR	I	INSTANTANEOUS		
AT	AMMETER TRIP (CIRCUIT BREAKER)	I/INST	INTERCOM MASTER	S	SHORT CIRCUIT AMPERE(S)
ATS	AUTOMATIC TRANSFER SWITCH	ICM	INTERCOM REMOTE	SCA	SMOKE DETECTOR
AUX	AUXILIARY	ICR	INTRUSION DETECTION SYSTEM	SD	SMOKE DUCT DETECTOR
A/V	AUDIO VISUAL	IDS	ISOLATED GROUND	SDD	SECONDARY
AWG	AMERICAN WIRE GAUGE	IG	INTERMEDIATE METAL CONDUIT	SEC	SUPPLY FAN
		IMC	INSTRUMENT	SF	SURGE PROTECTIVE DEVICE
		INSTR		SPD	SPECIFICATION
B	BOILER	J	JUNCTION BOX	SPKR	SPEAKER
BAS	BUILDING AUTOMATION SYSTEM	J, J/B	JUNCTION BOX	SS	STAINLESS STEEL/SOLID STATE
BFC	BELOW FINISHED CEILING			ST	SHUNT TRIP/SHORT TIME
BKR	BREAKER			STD	STANDARD
BLDG	BUILDING			STP	SHIELDED TWISTED PAIR
BP	BYPASS			STS	STATIC TRANSFER SWITCH
BSC	BIOLOGICAL SAFETY CABINET			SW	SWITCH
				SWBD	SWITCHBOARD
				SWGR	SWITCHGEAR
				SYS	SYSTEM
C	CONDUCTOR	K	KEY LOCK (KEY INTERLOCK SCHEME)		
C CDT	CONDUIT	KA	KILOAMPERE(S)		
CATV	CABLE TELEVISION	KCM	THOUSAND CIRCULAR MILS		
CB	CIRCUIT BREAKER	KEF	KITCHEN EXHAUST FAN		
CCTV	CLOSED CIRCUIT TELEVISION	KWH	KILOWATT		
CKT	CIRCUIT	KV	KILOWATT HOUR		
CLG	CEILING	KVA	KILOWOLT-AMPERE(S)		
CO	CONDUIT ONLY	KVAR	KVA REACTIVE	T, TRANSF	TRANSFORMER
COAX	COAXIAL CABLE	L	LOCKING TYPE/LOAD	TB, T/B	TERMINAL BOX
COL	COLUMN	LA	LIGHTNING SURGE ARRESTOR	TEL	TELEPHONE
COMM	COMMUNICATIONS	LAB	LABORATORY	TEMP	TEMPERATURE
COMP	COMPRESSOR	LAN	LOCAL AREA NETWORK	TV	TELEVISION
CONT	CONTROL	LOG	LOOKOUT GALLERY	TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSION
COR	CONTRACTING OFFICER REPRESENTATIVE	LP	LIGHTING PANEL	TYP	TYPICAL
CP	CONTROL PANEL	LT	LONG TIME		
CPT	CONTROL PANEL TRANSFORMER	LTC	LIGHTING		
CPU	CENTRAL PROCESSING UNIT	LTS	LIGHTS		
CR	CARD READER				
CRT	CATHODE RAY TUBE MONITOR				
CS	CONTROL SWITCH				
CT	CURRENT TRANSFORMER				
CU	COPPER				
CUH	CABINET UNIT HEATER				
D	DEPTH	M	METER(S)		
DC	DIRECT CURRENT	MAX	MAXIMUM		
DDC	DIRECT DIGITAL CONTROL	MCB	MAIN CIRCUIT BREAKER		
DED	DEDICATED	MCC	MOTOR CONTROL CENTER		
DEMO	DEMOLITION	MDF	MOLDED CASE CIRCUIT BREAKER		
DIA	DIAMETER	MECH	MAIN DISTRIBUTION FRAME		
DISC	DISCONNECT	MFR	MECHANICAL		
DIST	DISTRIBUTION	MH	MANUFACTURER		
DN	DOWN	MI	MANHOLE		
DWG	DRAWING	MIC	MINERAL-INSULATED		
		MIN	MEDIA INTERFACE CONNECTOR		
		MLO	MINIMUM		
		MM	MAIN LUGS ONLY		
		MM2	MILLIMETER(S)		
		MP	MILLIMETER(S) SQUARED		
		MPS	MAIN PANEL		
		MTD	MANUAL PULL STATION		
		MTG	MOTOR STARTER		
		MTG	MOUNT/MOUNTED		
		MTG	MOUNTING		
		MTS	MANUAL TRANSFER SWITCH		
		MV	MEDIUM VOLTAGE		
E	EXISTING TO REMAIN	N	NEW		
E, ELEC	ELECTRIC	N	NEUTRAL		
EC	ELECTRIC CONTRACTOR, EMPTY CONDUIT	NC	NORMALLY CLOSED		
EF	EXHAUST FAN	NEC	NATIONAL ELECTRIC CODE		
EL, ELEV	ELEVATION	NC	NOT IN CONTRACT		
EM	EMERGENCY	NO	NORMALLY OPEN		
EMT	ELECTRICAL METAL TUBING	NO.	NUMBER		
EO	ELECTRICALLY OPERATED	NORM	NORMAL		
EOL	END OF LINE DEVICE	NTS	NOT TO SCALE		
EPO	EMERGENCY POWER OFF				
EQ	EQUAL				
EQUIP	EQUIPMENT				
ER	EXISTING TO BE RELOCATED				
ETR	EXISTING TO REMAIN				
EUH	ELECTRIC UNIT HEATER				
EW	ELECTRIC WATER COOLER				
EXIST	EXISTING				
F	FLUSH	O	ON CENTER		
FA	FIRE ALARM	OC	OVERLOAD		
FACP	FIRE ALARM CONTROL PANEL	OCB	OIL CIRCUIT BREAKER		
FCC	FIRE COMMAND CENTER	OL	OVERLOAD		
FCU	FAN COIL UNIT	OS	OCCUPANCY SENSOR		
FDDI	FIBER DISTRIBUTED DATA INTERFACE				
FDR	FEEDER				
FIN FL	FUME HOOD	P	POLE		
FIP	FINISHED FLOOR	PA	PUBLIC ADDRESS SYSTEM		
FIXT	FIELD INTERFACE PANEL	PB	PUSH BUTTON/PULL BOX		
FLA	FIXTURE	PBX	PRIVATE BRANCH EXCHANGE		

GENERAL REQUIREMENTS

E.1 THE WORK TO BE DONE UNDER THIS PROJECT INCLUDES PROVIDING ALL EQUIPMENT, MATERIALS, LABOR, AND SERVICES, AND PERFORMING ALL OPERATIONS FOR COMPLETE AND OPERATING SYSTEMS. ANY WORK NOT SPECIFICALLY COVERED, BUT NECESSARY TO COMPLETE THIS INSTALLATION, SHALL BE PROVIDED. ALL EQUIPMENT AND WIRING TO BE NEW AND PROVIDED UNDER THIS CONTRACT UNLESS OTHERWISE NOTED.

E.2 ENTIRE INSTALLATION, INCLUDING MATERIALS, EQUIPMENT AND WORKMANSHIP, SHALL CONFORM TO THE 2008 EDITION OF THE NATIONAL ELECTRIC CODE (NFPA 70 AND NECA-1) AS WELL AS ALL APPLICABLE LAWS AND REGULATIONS AND REGULATORY BODIES HAVING JURISDICTION OVER THIS WORK.

E.3 THE TERM "FURNISH" SHALL MEAN TO OBTAIN AND SUPPLY TO THE JOB SITE. THE TERM "INSTALL" SHALL MEAN TO FIX IN POSITION AND CONNECT FOR USE. THE TERM "PROVIDE" SHALL MEAN TO FURNISH AND INSTALL. THE TERM "CONTRACTOR" SHALL MEAN ELECTRICAL CONTRACTOR.

E.4 ONLY WRITTEN CHANGES AND/OR MODIFICATIONS APPROVED BY THE ARCHITECT, CONSULTING ENGINEER OR OWNER'S REPRESENTATIVE WILL BE RECOGNIZED.

E.5 ALL NEW ELECTRICAL MATERIAL AND EQUIPMENT SHALL BE LISTED BY UNDERWRITERS' LABORATORIES, INC. (UL) AND BEAR THE UL LABEL.

E.6 PROVIDE ALL SCAFFOLDING, LADDERS, RIGGING, HOSTING, ETC, FOR THIS WORK.

E.7 PROVIDE TECHNICAL MANUALS, PER SPECIFICATIONS, AND GIVE INSTRUCTIONS TO USER FOR ALL EQUIPMENT AND SYSTEMS PROVIDED UNDER THIS CONTRACT AFTER ALL ARE CLEANED AND OPERATING.

E.8 THE DRAWINGS ARE DIAGRAMMATIC AND ALL SPECIALTIES AND APPURTENANCES ARE NOT SHOWN, BUT SHALL BE PROVIDED AS REQUIRED.

E.9 CONTRACTOR SHALL FIELD VERIFY DIMENSIONS OF FINISHED CONSTRUCTION PRIOR TO FABRICATION AND INSTALLATION OF FIXTURES AND EQUIPMENT.

E.10 THE WORK SHALL INCLUDE ALL PANELS, DEVICES, FEEDERS AND BRANCH CIRCUIT WIRING AS REQUIRED FOR THE DISTRIBUTION SYSTEM INDICATED AND CALLED FOR ON THE DRAWINGS, REQUIRED BY SPECIFICATIONS AND AS NECESSARY FOR COMPLETE FUNCTIONAL SYSTEMS PRESENTED AND INTENDED.

E.11 CONTRACTOR SHALL FURNISH ALL MATERIAL, LABOR, TOOLS, EQUIPMENT, CONSUMABLES AND SERVICES REQUIRED FOR OBTAINING, DELIVERY, INSTALLATION, CONNECTION, DISCONNECTION, REMOVAL, RELOCATION, REPAIR, REPLACEMENT, TESTING AND COMMISSIONING OF ALL EQUIPMENT AND DEVICES INCLUDED IN OR NECESSARY FOR THE WORK, AS APPLICABLE.

E.12 ELECTRICAL WORK SHALL INCLUDE ALL REQUIRED CUTTING, PATCHING AND THE FULL RESTORATION OF WALL AND FLOOR STRUCTURE AND SURFACES.

E.13 EXACT ROUTING OF CONDUITS SHALL BE DETERMINED IN THE FIELD.

E.14 CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH ALL CONDITIONS AND SYSTEMS THAT EFFECT HIS BIDDING AND WORK, AND SHALL PROVIDE VALUE FOR SAME IN HIS BID.

E.15 UPON COMPLETION OF THE ELECTRICAL WORK, CONTRACTOR SHALL TEST THE COMPLETE ELECTRICAL SYSTEM FOR SHORTS, GROUNDS, AND PROPER OPERATION, IN THE PRESENCE OF THE OWNER'S REPRESENTATIVE.

E.16 UPON COMPLETION OF WORK, THE CONTRACTOR SHALL CLEAN AND ADJUST ALL EQUIPMENT AND LIGHTING AND TEST SYSTEMS TO THE SATISFACTION OF OWNER AND ENGINEER. RESULTS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL.

E.17 ALL WORK SHALL BE PERFORMED BY THOSE SKILLED IN THEIR PARTICULAR TRADE IN A NEAT AND WORKMANLIKE MANNER.

E.18 ELECTRICAL WORK SHALL BE DONE AT SUCH A TIME, AND IN SUCH MANNER, AS WILL LEAST INTERFERE WITH THE MAINTENANCE AND OPERATION OF THE SITE'S AND/OR BUILDING'S ACTIVITIES. PROVISIONS SHALL BE MADE TO PERMIT THE USE OF ALL EXISTING ELECTRICAL SYSTEMS AT ALL TIMES. PROVIDE TEMPORARY FACILITIES TO SECURE THESE CONDITIONS AND REMOVE SUCH TEMPORARY FACILITIES WHEN NO LONGER REQUIRED.

E.19 SHUTDOWN WORK SHALL BE SCHEDULED AT SUCH TIME AND IN SUCH MANNER AS DIRECTED BY THE OWNER AND ENGINEER. PROVIDE A MINIMUM ONE WEEK NOTICE.

E.20 WHERE ALLOWABLE SHUTDOWN PERIODS CANNOT BE OF DURATION TO ACCOMMODATE ALL OF THE REQUIRED WORK, THE CONTRACTOR SHALL PERFORM THE WORK IN A SERIES OF PREPLANNED STAGES DURING ALLOWABLE SHUTDOWN PERIODS. PROVIDE TEMPORARY FACILITIES TO ALLOW RE-ENERGIZING OF SERVICES BETWEEN WORKING STAGES.

PROJECT COORDINATION

PC.1 VERIFY FIELD CONDITIONS AT THE SITE AND NOTIFY THE OWNER OF ANY DISCREPANCIES, PRIOR TO COMMENCING WITH THE WORK.

PROTECTION OF WORK

PW.1 EFFECTIVELY PROTECT ALL MATERIALS AND EQUIPMENT FROM ENVIRONMENTAL AND PHYSICAL DAMAGE UNTIL FINAL ACCEPTANCE. CLOSE AND PROTECT ALL OPENINGS DURING CONSTRUCTION. PROVIDE NEW MATERIALS AND EQUIPMENT TO REPLACE ITEMS DAMAGED.

RACEWAYS

RW.1 ALL EXPOSED CONDUIT IN WET AND DAMP AREAS SHALL BE STEEL RMC (RIGID METAL CONDUIT), EXPOSED AND DRY AREAS SHALL BE EMT (ELECTRICAL METALIC TUBING). UNDERGROUND POWER CONDUIT SHALL BE CONCRETE ENCASED RNC (RIGID NONMETALLIC CONDUIT). CONCRETE SHALL BE REINFORCED WITH #4 REBAR IN CORNERS AND ON 1' SPACING TOP AND BOTTOM.

RW.2 CONDUIT SHALL BE RUN AT RIGHT ANGLES AND PARALLEL TO BUILDING LINES, SHALL BE NEATLY RACKED, AND SECURELY FASTENED. JUNCTION BOXES SHALL BE PROVIDED WHERE REQUIRED TO FACILITATE INSTALLATION OF WIRES.

RW.3 ALL CONDUIT AND ELECTRICAL EQUIPMENT SHALL BE SUPPORTED FROM THE BUILDING STRUCTURE IN AN APPROVED MANNER.

RW.4 ARRANGEMENT OF CONDUIT AND EQUIPMENT SHALL BE AS REQUIRED TO AVOID INTERFERENCES.

RW.5 FOR CONDUITS CROSSING EXPANSION JOINTS, PROVIDE EXPANSION FITTINGS FOR SIZE 1-1/4", AND LARGER. PROVIDE SECTIONS OF FLEXIBLE CONDUIT WITH GROUNDING JUMPERS FOR SIZES 1" AND SMALLER.

GROUNDING

RW.6 UNDERGROUND AND UNDER SLAB CONDUITS SHALL BE MINIMUM 1".

RW.7 INSTALL DETECTABLE UNDERGROUND TAPES FOR THE PROTECTION, LOCATION, AND IDENTIFICATION OF UNDERGROUND CONDUIT INSTALLATIONS.

RW.8 CONDUITS WITHOUT DESIGNATED SIZE SHALL BE 3/4".

A. RACEWAYS:

1. EMT: ANSI C80.3, ZINC-COATED STEEL, WITH SETSCREW OR COMPRESSION FITTINGS.
2. EMT: NEMA TC 13, COMPLYING WITH UL 1653.
3. FMC: ZINC-COATED STEEL.
4. IMC: ANSI C80.6, ZINC-COATED STEEL, WITH THREADED FITTINGS.
5. LFMC: ZINC-COATED, FLEXIBLE STEEL WITH SUNLIGHT-RESISTANT AND MINERAL-OIL-RESISTANT PLASTIC JACKET.
6. RNC: NEMA TC 2, TYPE EPC-40-PVC, WITH NEMA TC3 FITTINGS.
7. RMC: GALVANIZED RIGID STEEL MANUFACTURED IN ACCORDANCE WITH ANSI C80.100T-DIP GALVANIZED INSIDE AND OUT TO PROVIDE GALVANIC CORROSION PROTECTION. ALSO, TOP COATED WITH A COMPATIBLE ORGANIC LAYER TO PROTECT AGAINST WHITE RUST.
8. RACEWAY FITTINGS: SPECIFICALLY DESIGNED FOR RACEWAY TYPE USED IN PROJECT.
9. WIREWAYS: SHEET METAL SIZED AND SHAPED, WITH SCREW COVERS.

BOXES AND ENCLOSURES

BE.1 ELECTRICAL BOXES AND ENCLOSURES SHALL BE CAST METAL, EXCEPT AS NOTED.

BE.2 MOUNTING HEIGHTS OF EQUIPMENT AND DEVICES SHALL BE AS INDICATED ON THE DRAWINGS. WHERE MOUNTING HEIGHTS ARE NOT GIVEN ON THE DRAWINGS, UTILIZE THE FOLLOWING MOUNTING HEIGHTS (ALL DIMENSIONS TO CENTERLINE OF BOX):

- A. RECEPTACLES (WALL MOUNTED) - 24" A.F.F.
- B. RECEPTACLES (EXTERIOR) - 24" ABOVE FINISHED GRADE
- C. LIGHTING SWITCHES AND CONTROLS - 48" A.F.F.
- D. PANELBOARDS AND CABINETS - 78" TO TOP OF ENCLOSURE

BE.3 WHERE MULTIPLE SWITCHES AND RECEPTACLES ARE INDICATED AT THE SAME LOCATION, THEY SHALL BE MOUNTED BEHIND A COMMON FACEPLATE.

BE.4 PROVIDE WHILE IN USE METALLIC COVERS FOR ALL OUTDOOR AND ALL GROUND FAULT CIRCUIT INTERRUPTER (GFCI) RECEPTACLES.

BE.5 NEMA RATINGS: PROVIDE NEMA 4X BOXES AND ENCLOSURES IN WET AND CORROSIVE AREAS. PROVIDE NEMA 3R FOR OUTDOOR AND WET AREAS. PROVIDE NEMA 7 FOR ALL CLASS 1, DIV. 1 & DIV. 2, EXCEPT PULL BOXES FOR DIV. 2.

BE.6 FIBERGLASS HANHOLES AND BOXES: MOLDED OF FIBERGLASS-REINFORCED POLYESTER RESIN, WITH FRAME AND COVERS OF FIBERGLASS. STANDARD: COMPLY WITH SCTE 77.

- A. CONFIGURATION: DESIGNED FOR FLUSH BURIAL WITH CLOSED BOTTOM UNLESS OTHERWISE INDICATED.
- B. COVER: WEATHERPROOF, SECURED BY TAMPER-RESISTANT LOCKING DEVICES AND HAVING STRUCTURAL LOAD RATING CONSISTENT WITH ENCLOSURE AND HANHOLE LOCATION.
- C. COVER FINISH: NONSKID FINISH SHALL HAVE A MINIMUM COEFFICIENT OF FRICION 0.50. COVER LEGEND: "MOLDED LETTERING, "ELECTRIC."
- D. CONDUIT ENTRANCE PROVISIONS: CONDUIT-TERMINATING FITTINGS SHALL MATE WITH ENTERING DUCTS FOR SECURE, FIXED INSTALLATION IN ENCLOSURE WALL.
- E. HANHOLES: 12 INCHES WIDE BY 24 INCHES LONG (300 MM WIDE BY 600 MM LONG) AND LARGER. HAVE INSERTS FOR CABLE RACKS AND PULLING-IN IRONS INSTALLED BEFORE CONCRETE IS POURED.

IDENTIFICATION

ID.1 TAPE MARKERS FOR WIRE: VINYL OR VINYL-CLOTH, SELF-ADHESIVE, WRAPAROUND TYPE WITH CIRCUIT IDENTIFICATION LEGEND MACHINE PRINTED BY THERMAL TRANSFER OR EQUIVALENT PROCESS.

ID.2 RACEWAY IDENTIFICATION MATERIALS: SELF-ADHESIVE, COLOR-CODING VINYL TAPE, FLEXIBLE, PREPRINTED, SELF-ADHESIVE VINYL, INDICATING L-L AND L-N VOLTAGES.

ID.3 SELF-ADHESIVE WARNING LABELS: FACTORY PRINTED, MULTICOLOR, PRESSURE-SENSITIVE ADHESIVE LABELS, CONFIGURED FOR DISPLAY ON FRONT COVER, DOOR, OR OTHER ACCESS TO EQUIPMENT UNLESS OTHERWISE INDICATED.

ID.4 EQUIPMENT IDENTIFICATION LABELS: ENGRAVED, LAMINATED ACRYLIC OR MELAMINE LABEL; PUNCHED OR DRILLED FOR SCREW MOUNTING. WHITE LETTERS ON A DARK-GRAY BACKGROUND; RED LETTERS FOR EMERGENCY SYSTEMS.

EQUIPMENT TO BE LABELED:

IDENTIFICATION LABELING OF SOME ITEMS LISTED BELOW MAY BE REQUIRED BY INDIVIDUAL SECTIONS OR BY NFPA 70.

- A. PANELBOARDS, ELECTRICAL CABINETS, AND ENCLOSURES.
- B. ELECTRICAL SWITCHGEAR AND SWITCHBOARDS.
- C. TRANSFORMERS.
- D. MOTOR-CONTROL CENTERS.
- E. DISCONNECT SWITCHES.
- F. ENCLOSED CIRCUIT BREAKERS.
- G. MOTOR STARTERS.
- H. PUSH-BUTTON STATIONS.
- I. POWER TRANSFER EQUIPMENT.
- J. CONTACTORS.

WIRING

W.1 POWER AND LIGHTING - TYPE THHN-2 IN CONDUIT OR TYPE MC CABLE IN DRY INTERIOR SPACES.

W.2 WHERE EQUIPMENT, LIGHTING FIXTURES AND WIRING DEVICES ARE SHOWN WITH CIRCUIT NUMBERS ONLY, THE MINIMUM BRANCH CIRCUITING REQUIREMENTS SHALL BE AS FOLLOWS:

- A. LIGHTING FIXTURES - (2) #12 & #12 GND.
- B. RECEPTACLES - (2) #12 & #12 GND.
- C. 20A, 277 OR 120V CIRCUITS - (2) #12 & #12 GND
- D. HOMERUNS TO PANEL BOARDS SHALL CONTAIN NO MORE THAN THREE CIRCUITS.

W.3 WIRE SIZES SHALL BE INCREASED TO COMPENSATE FOR VOLTAGE DROP. INCREASE WIRE SIZE TO COMPENSATE FOR VOLTAGE DROP FOR 20 AMP CIRCUITS AS FOLLOWS:

- A. 120V/1# CIRCUITS LONGER THAN 80' SHALL UTILIZE MIN. #10 AWG.
- B. 208V/3# CIRCUITS LONGER THAN 110' SHALL UTILIZE MIN. #10 AWG.
- C. 277V/1# CIRCUITS LONGER THAN 130' SHALL UTILIZE MIN. #10 AWG.
- D. 480V/3# CIRCUITS LONGER THAN 260' SHALL UTILIZE MIN. #10 AWG.

W.4 ALL CONDUCTORS IN CONDUIT SHALL BE STRANDED EXCEPT 120V RECEPTACLE WIRING.

WIRING DEVICES

WD.1 STRAIGHT-BLADE RECEPTACLES

A. CONVENIENCE RECEPTACLES, 125 V, 20 A: COMPLY WITH NEMA WD 1, NEMA WD 6 CONFIGURATION 5-20R, UL 498, AND FS W-C-596.

TOGGLE SWITCHES

A. COMPLY WITH NEMA WD 1, UL 20, AND FS W-S-896. SWITCHES, 120/277 V, 20 A.

CONDUIT SUPPORTS AND HANGERS

SH.1 MOUNTING, ANCHORING, AND ATTACHMENT COMPONENTS:

- A. POWDER-ACTUATED FASTENERS: THREADED-STEEL STUD.
- B. MECHANICAL-EXPANSION ANCHORS: INSERT-WEDGE-TYPE, STAINLESS STEEL, FOR USE IN HARDENED PORTLAND CEMENT CONCRETE.
- C. CONCRETE INSERTS: STEEL OR MALLEABLE-IRON, SLOTTED-SUPPORT SYSTEM UNITS SIMILAR TO MSS TYPE 18; COMPLYING WITH MFMA-3 OR MSS SP-58.
- D. CLAMPS FOR ATTACHMENT TO STEEL STRUCTURAL ELEMENTS: MSS SP-58, TYPE SUITABLE FOR ATTACHED STRUCTURAL ELEMENT.
- E. THROUGH BOLTS: STRUCTURAL TYPE, HEX HEAD, HIGH STRENGTH; COMPLYING WITH ASTM A 325.
- F. TOGGLE BOLTS: ALL-STEEL SPRINGHEAD TYPE.
- G. HANGER RODS: THREADED STEEL.

SH.2 SUPPORT, ANCHORAGE, AND ATTACHMENT COMPONENTS

STEEL SLOTTED SUPPORT SYSTEMS: COMPLY WITH MFMA-4, FACTORY FABRICATED COMPONENTS FOR FIELD ASSEMBLY.

MANUFACTURERS SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS BY ONE OF THE FOLLOWING:

1. ALLIED TUBE & CONDUIT.
2. COOPER B-LINE, INC.; A DIVISION OF COOPER INDUSTRIES.
3. ERICO INTERNATIONAL CORPORATION.
4. CS METALS CORP.
5. THOMAS & BETTS CORPORATION.
6. UNISTRUT; TYCO INTERNATIONAL, LTD.
- A. METALLIC COATINGS: HOT-DIP GALVANIZED AFTER FABRICATION AND APPLIED ACCORDING TO MFMA-4.
- B. STAINLESS STEEL: TYPE 316 IN ACCORDANCE WITH ASTM A240.
- C. NONMETALLIC COATINGS: MANUFACTURER'S STANDARD PVC, POLYURETHANE, OR POLYESTER COATING APPLIED ACCORDING TO MFMA-4.
- D. CHANNEL DIMENSIONS: SELECTED FOR APPLICABLE LOAD CRITERIA.

ELECTRICAL EQUIPMENT REQUIREMENTS

EE.1 ELECTRICAL PANELS, ELECTRICAL SERVICE MAIN SWITCHES/CIRCUIT BREAKERS, AND CONTROL CABINETS SHALL BE MOUNTED A MAXIMUM OF 6'7" TO MID POINT OF HANDLE.

EE.2 ANY EQUIPMENT FED WITH SERVICE ENTRANCE CONDUCTORS SHALL BE RATED FOR A SERVICE ENTRANCE.

EE.3 THE AIC RATING OF THE EQUIPMENT COINCIDE WITH THE EQUIPMENT UPSTREAM, U.O.N.

EE.4 COLOR CODING:

A. COLOR-CODING FOR PHASE AND VOLTAGE LEVEL IDENTIFICATION, 600 V AND LESS: UNGROUNDED SERVICE, FEEDER, AND BRANCH-CIRCUIT CONDUCTORS.

1. COLORS FOR 208/120-V CIRCUITS:
 - PHASE A: BLACK.
 - PHASE B: RED.
 - PHASE C: BLUE.
2. COLORS FOR 480/277-V CIRCUITS:
 - PHASE A: BROWN.
 - PHASE B: ORANGE.
 - PHASE C: YELLOW.

B. FIELD-APPLIED, COLOR-CODING CONDUCTOR TAPE: APPLY IN HALF-LAPPED TURNS FOR A MINIMUM DISTANCE OF 6 INCHES (150 MM) FROM TERMINAL POINTS.

FIRE STOPPING

F.1 APPLY FIRESTOPPING TO ELECTRICAL PENETRATIONS OF FIRE-RATED FLOOR AND WALL ASSEMBLIES TO RESTORE ORIGINAL FIRE-RESISTANCE RATING OF ASSEMBLY.

F.2 INSTALL FORMING MATERIALS AND OTHER ACCESSORIES OF TYPES REQUIRED TO SUPPORT FILL MATERIALS DURING THEIR APPLICATION AND IN THE POSITION NEEDED TO PRODUCE CROSS-SECTIONAL SHAPES AND DEPTHS REQUIRED TO ACHIEVE FIRE RATINGS INDICATED.

1. AFTER INSTALLING FILL MATERIALS AND ALLOWING THEM TO FULLY CURE, REMOVE COMBUSTIBLE FORMING MATERIALS AND OTHER ACCESSORIES NOT INDICATED AS PERMANENT COMPONENTS OF FIRESTOPPING.
2. INSTALL FILL MATERIALS FOR FIRESTOPPING BY PROVEN TECHNIQUES TO PRODUCE THE FOLLOWING RESULTS:
 1. FILL Voids AND CAVITIES FORMED BY OPENINGS, FORMING MATERIALS, ACCESSORIES, AND PENETRATING ITEMS AS REQUIRED TO ACHIEVE FIRE-RESISTANCE RATINGS INDICATED.
 2. APPLY MATERIALS SO THEY CONTACT AND ADHERE TO SUBSTRATES FORMED BY OPENINGS AND PENETRATING ITEMS.
 3. FOR FILL MATERIALS THAT WILL REMAIN EXPOSED AFTER COMPLETING THE WORK, FINISH TO PRODUCE SMOOTH, UNIFORM SURFACES THAT ARE FLUSH WITH ADJOINING FINISHES.

MOUNTING HEIGHTS

MH.1 UNLESS OTHERWISE INDICATED, OUTLET BOXES IN WALLS SHALL BE LOCATED WITH CENTERLINE AT THE FOLLOWING ELEVATIONS ABOVE THE FINISHED FLOOR (AFF) LINE. VERIFY ALL HEIGHTS WITH THE GENERAL CONSTRUCTION CONTRACTOR PRIOR TO ACTUAL LAYOUT OF WORK.

A. SWITCH OUTLETS	4'-0" AFF
B. BRACKET OUTLETS (STAIRS)	7'-0" AFF
C. BRACKET OUTLETS (OTHER)	6'-6" AFF
D. RECEPTACLE OUTLETS (JUN)	1'-6" AFF
E. RECEPTACLE OUTLETS, MECHANICAL ROOMS	3'-0" AFF
F. RECEPTACLE OUTLETS MOUNTED, ABOVE CASEWORK/CABINETS	0'-8" ABOVE COUNTERTOP
G. CLOCK OUTLETS	1'-0" BELOW CEILING
H. MOTOR STARTERS AND SAFETY SWITCHES	4'-6" AFF
I. PANELBOARDS (TOP)	6'-6" AFF
J. DATA/TELEPHONE	1'-6" AFF
K. TELEPHONE	4'-0" AFF

MOUNTING HEIGHT NOTE: THE ABOVE MOUNTING HEIGHTS SHALL BE ADHERED TO UNLESS OTHERWISE NOTED ON PLANS OR SPECIFICATIONS.

LIGHTING CONTROLS

LC.1 24-HOUR MECHANICAL TIME SWITCH SHALL BE INTERMATIC MODEL T101PCD82 OR APPROVED EQUAL, 120VAC, 60 HZ, SPST, INDOOR/OUTDOOR TYPE 3R PLASTIC WITH SEE THROUGH DOOR ENCLOSURE, COLOR GRAY, WITH 1 HOUR INTERVALS.

CODES

C.1 THE ENTIRE INSTALLATION, INCLUDING MATERIALS, EQUIPMENT AND WORKMANSHIP, SHALL CONFORM TO APPLICABLE LAWS AND REGULATIONS AND REGULATORY BODIES HAVING JURISDICTION OVER THIS WORK.

C.2 NATIONAL ELECTRICAL CODE: NEC 2017

C.3 NFPA 72, NATIONAL FIRE ALARM CODE

C.4 INTERNATIONAL BUILDING CODE 2018, NEW JERSEY EDITION

C.5 INTERNATIONAL MECHANICAL CODE 2018.

SCOPE OF WORK

1. CONTRACTOR SHALL VERIFY EXISTING LIGHTING CIRCUITS, PLUG TYPES AND FIXTURE LOCATIONS.
2. CONTRACTOR SHALL VERIFY LIGHTING PANEL LOAD DIRECTORIES.
3. PROVIDE NEW RACEWAYS AND WIRING AS INDICATED. REPLACE DAMAGED OR MISSING RACEWAYS AND CIRCUITS AS REQUIRED FOR A COMPLETE SYSTEM.
4. ALL CIRCUIT WIRING SHALL BE NEW AND WIRED TO CIRCUITS INDICATED ON PLANS.
5. PROVIDE NEW CIRCUIT BREAKERS AND UPDATE PANEL SCHEDULES.
6. PROVIDE NEW LIGHTING FIXTURES AS INDICATED ON DRAWINGS.
7. COORDINATE WITH OWNER TO CONFIGURE LIGHTING CONTROLS AND SEQUENCE.
8. TEST ALL FINISHED WORK INCLUDING CIRCUITING, CONTROLS, CIRCUIT BREAKERS AND LIGHT FIXTURES.
9. PROVIDE LIGHTING CONTROL SYSTEM (LIGHT TIMERS AND DIMMER SWITCHES) FOR EXTERIOR LIGHTS PER SPECIFICATIONS ON DRAWING E-002.
10. SEE KEYED NOTES FOR ADDITIONAL INFORMATION.


ELECTRICAL
GENERAL NOTES

crane associates, p.c.
CONSULTING ENGINEERS / ARCHITECTS
92 East Main Street, Suite 200, Somerville, NJ 08876-3109
www.craneassociates.com

Edward Quaranta, P.E.
Professional Engineer NJ Lic. No. 24560661100
Date: 10/20/2025



MSU COURTYARD LIGHTING
UNIVERSITY HALL
1 NORMAL AVENUE
MONTCLAIR, NJ 07043

PROJECT NO.
6780-2501
DRAWING NO.
E-002
DWG 6 OF 9



1 UNIVERSITY HALL COURTYARD ELECTRICAL FLOOR PLAN

Scale: 3/16" = 1'-0"



2 ELECTRICAL ROOM ENLARGED PLAN

Scale: 3/8" = 1'-0"

GENERAL NOTES

1. FOR GENERAL NOTES, ABBREVIATIONS AND SPECIFICATION SEE E0.01
2. PAINT CONDUIT TO MATCH POST.
3. CIRCUITS SHOWN DIAGRAMATICALLY. COORDINATE WITH A/E
4. EXTERIOR CONDUIT SHALL BE RIGID STEEL. INTERIOR CONDUIT SHALL BE EMT.

ELECTRICAL KEYED NOTES

(E01) 1. OVERHEAD CONDUCTORS FOR FESTOON LIGHTING SHALL NOT BE SMALLER THAN 12 AWG UNLESS THE CONDUCTORS ARE SUPPORTED BY MESSENGER WIRES.
2. THE CONDUCTORS SHALL BE SUPPORTED BY MESSENGER WIRE IN ALL SPANS.
3. THE MESSENGER WIRE SHALL BE SUPPORTED BY STRAIN INSULATORS.
4. CONDUCTS OR MESSENGER WIRES SHALL NOT BE ATTACHED TO ANY FIRE ESCAPE, DOWNSPOUT, OR PLUMBING EQUIPMENT.

(E02) PROVIDE WEATHER PROOF NEMA 3R JUNCTION BOX.

(E03) CONTRACTOR SHALL VERIFY PANEL IN FIELD.

(E04) WIRE CIRCUITS TO PANEL P2N1A4 IN ELECTRICAL ROOM AS INDICATED.

(E05) APPROXIMATE LOCATION OF ELECTRICAL ROOM. SEE ENLARGED PLAN.

(E06) FESTOON LIGHTING DISTANCE IS LIMITED TO 100' BY MANUFACTURER. PROVIDE MULTIPLE STRING LIGHTS AS REQUIRED.

FEEDER SCHEDULE

(F1) 2#12 AND 1#12 GROUND IN 1" CONDUIT



crane associates, p.c.
consulting engineers/architects
92 East Main Street, Suite 200, Somerville, NJ 08876-3109
www.cranesassociates.com

Edward Quaranta, P.E.
Professional Engineer NJ Lic. No. 24650661100
Date: 10/20/2025

MSU COURTYARD LIGHTING
UNIVERSITY HALL
1 NORMAL AVENUE
MONTCLAIR, NJ 07043

ELECTRICAL
NEW WORK FLOOR PLAN
PROJECT NO.
6780-2501

DRAWING NO.
E-101
DWG. 7 OF 9

(E) PANEL P2N1A4 208/120V 3Ø 4W, 250A MLO & GROUND BUS											
CIR. NO.	RATING (A)	DESCRIPTION	CONNECTED LOAD (kVA)			CONNECTED LOAD (kVA)			DESCRIPTION	RATING (A)	CIR. NO.
			A	B	C	A	B	C			
1	20A 1P	RECEPTS-CLASS	0.8			0.8			POWER FOR SC	20A 1P	2
3	20A 1P	RECEPTS-CLASS		0.8			0.8		POWER FOR SC	20A 1P	4
5	20A 1P	RECEPTS-CLASS			0.8		0.8		RECEPTS-CLASS	20A 1P	6
7	20A 1P	RECEPTS-CLASS	0.8			0.8			RECEPTS-CLASS	20A 1P	8
9	20A 1P	RECEPTS-CLASS		0.8			0.8		PROJECTOR	20A 1P	10
11	20A 1P	RECEPTS-CLASS			0.8		0.8		PROJECTOR SCREEN	20A 1P	12
13	20A 1P	RECEPTS-CLASS	0.8								14
15											16
17											18
19											20
21											22
23											24
25											26
27											28
29											30
31											32
33											34
35	20A 1P	TF-1			0.6						36
37	20A 1P	RCPT - ELEC. RM	0.6								38
39	20A 1P	RCPT - ELEV. PIT		0.6		0.6	COURTYARD STRING LIGHTS	20A 1P	40		
41	20A 1P	RCPT - ELEV. PIT			0.6		1	LOBBY LIGHTING	20A 1P	42	
10,00AIC RATING			PHASE SUB TOTAL:	3	2.2	2.8	1.6	2.2	2.6		
			SUB TOTAL:		8			6.4			
			TOTAL:				14.4				

ELECTRICAL KEYED NOTES

E01 PROVIDE NEW CIRCUIT BREAKER, BREAKER SHALL MATCH EXISTING AIC RATING. CONNECT TO NEW COURTYARD STRING LIGHTS AS INDICATED. CONTRACTOR TO VERIFY. NOTIFY A/E OF ANY DISCREPANCIES.

DESIGNED	EQ
DRAWN	CK
CHECKED	EQ
SCALE AS SHOWN	
DATE: 10/20/2025	
NO. BY CK	
DATE:	
REVISION N	


MSU COURTYARD LIGHTING
UNIVERSITY HALL
1 NORMAL AVENUE
MONTCLAIR, NJ 07043

ELECTRICAL
SCHEDULES


PROJECT NO.
6780-2501
DRAWING NO.
E-401
DWG 8 OF 9

LIGHTING FIXTURE SCHEDULE							
SIMPLE	MANUFACTURER	CATALOG NO.	DESCRIPTION	LAMP	WATTAGE	Mounting Height	Notes
—○—○—	CALI	ML2999-CB-3.0K-GSFL-DM-WETPA-BK	STRING LIGHTS	LED	3W	10'	LINEAR FT PER DRAWINGS


PROJECT NO.
6780-2501
DRAWING NO.
E-401
DWG 8 OF 9




1 E-501 **PENETRATION THROUGH CONCRETE WALL**
Scale: N.T.S.



2 E-501 **PENETRATION THROUGH CONCRETE FLOOR**
Scale: N.T.S.



3 E-501 **COURTYARD STRING LIGHTS RISER DIAGRAM**
Scale: N.T.S.



4 E501 **DIRECT BURIED SECONDARY DETAIL**
Scale: NONE
NOTES:
1 1" PVC CONDUIT, POWER, ACTIVE

GENERAL NOTES

1. FOR GENERAL NOTES, ABBREVIATIONS AND SPECIFICATION SEE E0.01
2. EXTERIOR CONDUIT ABOVE GRADE SHALL BE RIGID STEEL. UNDERGROUND CONDUIT SHALL BE PVC. INTERIOR CONDUIT SHALL BE EMT.

FEEDER SCHEDULE

F1 2#12 AND #12 GROUND IN 1" CONDUIT

MSU COURTYARD LIGHTING
UNIVERSITY HALL
1 NORMAL AVENUE
MONTCLAIR, NJ 07043

ELECTRICAL
DETAILS

PROJECT NO.
6780-2501
DRAWING NO.
E-501
DWG. 9 OF 9

crane associates, p.c.
CONSULTING ENGINEERS / ARCHITECTS
92 East Main Street, Suite 200, Somerville, NJ 08876-3109
www.cranassociates.com
Edward Quaranta, P.E.
Professional Engineer NJ Lic. No. 2465066100
Date: 10/20/2025

DESIGNED BY
DRAWN BY
CHECKED BY
SCALE AS
DATE 10/20/2025
NO. BY CK DATE
REVISION N